

Product data sheet

Item No. 96.232.2003.0

Cable assembly RST20i3K1B- 15P 20GL

RST 20i3/2 connection cable female - free end, 3 pole, assembled with shrinkage tube, application 250V, 16A, cable type H05VV-F, length 2.0m, cross section 1.5mm², coding-color light grey



Item No.	96.232.2003.0
EAN	4015573761247
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Shrinkage tube
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h)
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends



Cable type	H05VV-F
Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	female
Version cable end 2	Free end
Screened	No

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung *U*	Buchse female
.0	lichtgrau light grey	N	RE
.1	schwarz black	L	

Typ/type: RST2013K1B- 15P .. GL = lichtgrau/light grey
SW = schwarz/black

Farbe/color	.F
schwarz/black	.1
lichtgrau/light grey	.0

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) example (colour: black, grey)	Typ type
96.232.XX03.1	XX in dm-Schritten	96.232.1003.1 = 10dm/L= 1000mm	RST2013K1B- 15P 10SW
96.232.XX03.0		96.232.1003.0	RST2013K1B- 15P 10GL
U6.232.XX03.1	XX in m-Schritten	U6.232.1203.1 = 12 m/L=12000mm	RST2013K1B- 15P X12SW
U6.232.XX03.0		U6.232.1203.0	RST2013K1B- 15P X12GL

Fertigerang nach DIN 71697/Tolerance system acc. to DIN 71697. / types 023 Stoffkreislauf- und Deklarationsliste nach DIN EN ISO 14001 für einbaufähige Bauteile.
 This DIN standard declares the working principle. According to the envelope system with Wieland document 00-500-5013, list of prohibited /
 principle the deviations of form and position are limited by the size tolerances.
 (degradable hazardous substances) to be declared

Fertigerang nach DIN 14901 TG 130 / 00 - Zeichnung, keine mechanischen Änderungen
 00 - drawing, no mechanical modifications allowed
 / 1 - Veränderung
 / 1 - change

2007	Legende	Name	Zeichnung Nr./Drawing No.
010000	TECH. BÜRO	K. B. B.	96.232.0403.0 01K
010000	TECH. BÜRO	K. B. B.	
010000	TECH. BÜRO	K. B. B.	

KONFEKT_LEITUNG
 Buchse-freies Ende/female-free end 1,5 qmm
 Crimpausführung/ K1 250V