

Product data sheet

Item No. 96.233.8000.1

Cable assembly RST20I3K1BS 25P 80SW

RST 20i3/2 extension cable female - male, 3 pole, assembled with shrinkage tube, application 250V, 20A, cable type H05VV-F, length 8.0m, cross section 2.5mm², coding-color black



Item No.	96.233.8000.1
EAN	4015573760264
Order Unit	5 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Shrinkage tube
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h)
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.2 mm



Version of cable	Female - male
Type of cord set	Extension cable
Version cable end 1	female
Version cable end 2	male

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continous temperature	100 °C

Dimensions

Total length	8 m
--------------	-----

Technical drawing

The drawing shows a female-to-male extension cable with two 2.5mm max 20A conductors. Dimensions include a length of ca. 82mm for the female end, ca. 93mm for the male end, and a total length of L ± 3%. Color coding for the female end (X*) is: PE (green/yellow), N (blue), and L (brown). For the male end (Y*), it is: N (blue), PE (green/yellow), and L (brown).

.F	Farbe colour	Codierung	Buchse female	Codierung
.0	lichtgrau light grey	N	PE	PE
.1	schwarz black			

Teile - Nr. / part - no. | L | Beispiel (Farbe: schwarz) / example (colour: black) | Typ / type

96.233.XX00.F XX in dm-Schritten | 96.233.1000.1 = 10dm/L=1000mm | RST2013K1BS 25P 10SW

U6.233.XX00.F XX in m-Schritten | U6.233.1200.1 = 12 m/L=12000mm | RST2013K1BS 25P X12SW

Typ/type: RST2013K1BS 25P .. GL = lichtgrau/light grey
SW = schwarz/black

Weitere Daten siehe Katalog / further data see catalog

96.233.0400.0 01K

KONFEKT_LEITUNG
Buchse-Stecker / male-female
pre-assembled cable