

Product data sheet
Item No. 96.232.5000.1
Cable assembly RST20I3K1BS 15P 50SW

RST 20i3/2 extension cable female - male, 3 pole, assembled with shrinkage tube, application 250V, 16A, cable type H05VV-F, length 5.0m, cross section 1.5mm², coding-color black



Item No.	96.232.5000.1
EAN	4015573761162
Order Unit	15 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Shrinkage tube
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h)
Cable type	H05VV-F
Cable colour	Black
Cable diameter	8.3 mm

Version of cable	Female - male
Type of cord set	Extension cable
Version cable end 1	female
Version cable end 2	male
Screened	No

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	5 m
--------------	-----

Technical drawing

.F	Farbe colour	Codierung Buchse female	Codierung Stecker male	Verriegelung locking
.0	lichtgrau light grey	N	PE	05.583.2953 schwarz / black
.1	schwarz black	L	L	05.583.2954 braun / brown

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
96.232.XX00.F	XX in dm-Schritten	96.232.1000.1 = 10dm/L = 1000mm	RST2013K1BS 15P 10SW
U6.232.XX00.F	XX in m-Schritten	U6.232.1200.1 = 12 m/L = 12000mm	RST2013K1BS 15P X12SW

Typ/type: RST2013K1BS 15P .. GL = lichtgrau/light grey
SW = schwarz/black

Fraktionierung nach General tolerance	ISO - Drahtung, keine manuelle Änderungen ISO - Drawing, no manual modifications allowed	Zeichnung Nr./Drawing No.	96.232.0400.0 01K
Werkstoff/Material	2005 Zinn/Sn Kupfer/Copper Messing/Brass	Parameter K	
Änderung/Revision		Wieland	