









## LEŠTÍCÍ PROGRAM - INOX - upínací otvor Ø 19 a 20 mm

<b>SISAL</b> 	<b>TYP</b>	<b>Obj.č.</b>	<b>φ x otvor</b>	<b>Max.otáčky</b>	
	VPR 100	913 289	φ 100 x 19 mm / šestihran	4 000	5
	VPR 150	913 290	φ 150 x 20 mm	2 800	2
	VPR 200	913 291	φ 200 x 20 mm	2 000	2
<b>BAVLNA</b> 	<b>TYP</b>	<b>Obj.č.</b>	<b>φ x otvor</b>	<b>Max.otáčky</b>	
	PR 100	913 292	φ 100 x 19 mm / šestihran	4 000	8
	PR 150	913 293	φ 150 x 20 mm	2 800	2
	PR 200	913 294	φ 200 x 20 mm	2 000	2
<b>MĚKKÁ BAVLNA</b> 	<b>TYP</b>	<b>Obj.č.</b>	<b>φ x otvor</b>	<b>Max.otáčky</b>	
	HPR 100	913 295	φ 100 x 19 mm / šestihran	4 000	8
	HPR 150	913 296	φ 150 x 20 mm	2 800	2
	HPR 200	913 297	φ 200 x 20 mm	2 000	2
<b>NOSIČE A DISTANČNÍ KROUŽKY</b> 	<b>TYP</b>	<b>Obj.č.</b>	<b>Nosič se skládá ze dvou částí : stopka 12 mm a závit M14</b>		
	M14 / M14	908 137	pro stroje : se závitem M14 - nosič M14 / M14	1	
	FG 12 / M14	907 897	s kleštinou - stopka 12 mm / M14 spojit s nosičem M14 / M14	1	
	20:14	908 326	distanční kroužek vnější φ 20 mm / vnitřní 14 mm	10	