







LEŠTÍČÍ PROGRAM

STANDARD - upínací otvor Ø 6,14,18 a 22 mm

FILC 	TYP	Obj.č.	ϕ x šířka x otvor		Max.otáčky	
	FPS 30	901 523	30 x 7 x 6	FDv 6-6	6 000	1
	FPS 45	901 524	45 x 9 x 6	FDv 6-6	4 500	1
	FPS 80	902 143	80 x 10 x 14	FDv 6-14	2 300	1
	FPS 100	902 144	100 x 20 x 14	FDv 8-14	1 800	1
	FPS 120	902 145	120 x 20 x 14	FDv 12-14	1 500	1
	FPS 150	902 146	150 x 25 x 18	FDv MK 1-18	1 300	1
	FPS 175	902 147	175 x 30 x 18	FDv MK 1-18	1 100	1
	FPS 200	902 148	200 x 30 x 22	FDv MK 2-22	1 000	1
TEXTIL PLÁTNO 	TYP	Obj.č.	ϕ x šířka x otvor	Nosič	Max.otáčky	
	SS 80/10	902 154	80 x 10 x 14	FDv 6-14	6 000	1
	SS 100/20	902 155	100 x 20 x 14	FDv 8-14	5 000	1
	SS 120/20	902 156	120 x 20 x 14	FDv 12-14	4 000	1
	SS 150/30	902 157	150 x 30 x 18	FDv MK 1-18	3 200	1
	SS 175/30	902 158	175 x 30 x 18	FDv MK 1-18	2 700	1
	SS 200/30	902 159	200 x 30 x 22	FDv MK 2-22	2 500	1
	SS 250/30	902 160	250 x 30 x 22	FDv MK 2-22	2 000	1
NOSIČE 	TYP	Obj.č.	Stopka mm	Pro kotouč ϕ x šířka x otvor		
	FDv 6-14	20 717 01	6	80 x 15 x 14		1
	FDv 8-14	20 719 01	8	100 x 20 x 14		1
	FDv 12-14	49 020 01	12	125 x 20 x 14		1